

A-M30, we trust it!



A-M30

► Stable & reliable

Super big aluminum housing.
Excellent heat dissipation.
Long service time.

► Excellent performance

Mitsubishi power module, power never reduces even after long time use, long communication distance.

► Easy operation

LED display, 99 channels.
4 programmable keys.
Friendly interface.



Standard accessories



Holder/screw



Power source Extension cord




Speaker microphone



Glass tube fuse(together with power source extension cord)

Optional accessories



Programming software



Programming cable



A-M30

FREQUENCY RANGE

VHF(MHz)	136-174
UHF(MHz)	400-470

GENERAL PARAMETER

Channel	99
Channel Spacing	12.5/25KHz
Voltage	12V/13.8VDC
Operation Temperature	-30°C~60°C
Frequency Stability	+/-2.5ppm
Weight	1Kg
Antenna Impedance	50Ω
CTCSS/CDCSS	Yes
Scan	Yes
DTMF	Yes
TOT	Yes
Squelch	9 levels
Alarm	Yes
High/low power switchable	5/15/25W 5/15/50W

RECEIVER

Sensitivity	0.25uv
Adjacent Channel Selectivity	70DB
Intermodulation Rejection	70DB
Spurious Respond	70DB
Audio Output Power	4.0W

TRANSMITTER

Output Power	25/50W
Spurious and Harmonics	70DB
Modulation	16KOF3E
FM Noise	40DB
Audio Frequency Distortion	3%
Mic Impedance	2.2KΩ

■ Due to technology advancements, the technical data of real products maybe slightly different from the above data.

■ The physical product may look slightly different from the picture.

Dealer Area

